

ADVANCED ILLUMINATION - AL295 MICROBRITE

Compact Area Lighting

SERIE-AL295 AL295 bar light





- High-performance compact line light
- Available in 76 mm (3 inch) increments up to 457 mm (18 inches)

PRODUCT DESCRIPTION

The AL295 is part of the Microbrite family of high performance, compact machine vision lights. Outperforming the competition with a high intensity output of 73 kLux at a working distance of 100mm. The AL295 is available is expandable sizes in 3" increments up to 18".

Power options include:

- C1 connector for use with DCS series controllers
- C5 connector for use with Pulsar 320 strobe controller
- Continuous in-line controller powered by 24V power supply
- Combination strobe/continuous in-line controller powered by 24V power supply
- Default-OFF strobe/continuous in-line controller powered by 24V power supply
- Flying/tinned leads powered by 24V power supply

Other Wavelength options:

- UV 365, 375, 385, 395, 405
- Royal blue 455
- Blue 470
- Cyan 505
- Green 530
- Amber 590
- Red orange 625
- Red 660
- Infrared 730, 850, 940
- White WHI

For enquiries or quotes for wavelength and power options not listed here please contact us.

SPECIFICATIONS

Approvals	CE, RoHS
Feed	C1, C5, IC, I3, I3S
IP Class	IP50
Life Span	50000 h

Temperature range from	0 °C
Temperature range to	60 °C
Wave-Length	WHI, 365, 375, 385, 395, 405, 455, 470, 505, 530, 590, 625, 660, 730, 850, 940

