

## LINEAR BACKLIGHT

SERIE-BL193

BL193 linear backlight



### PRODUCT DESCRIPTION

Our Medium Intensity Linear Backlights provide rugged construction for demanding environments.

Medium intensity illumination with low power input requirements.

Multiple wavelengths available with very consistent illumination over the entire active area.

Available in 1" (25mm) increments with lengths up to 80.5" (2044mm).

## SPECIFICATIONS

<b>Approvals</b>	CE, RoHS
<b>Feed</b>	C1, C5, IC, I3, I3S, 24, M12
<b>IP Class</b>	IP64
<b>Life Span</b>	50000 h
<b>Temperature range from</b>	0 °C
<b>Temperature range to</b>	60 °C
<b>Wave-Length</b>	WHI, 470, 520, 660, 880



DIMENSIONS ARE IN MILLIMETRES (INCHES)

Sampling of Part Numbers/Dimensions

Part #	Length (mm) (Inches)	Part #	Length (mm) (Inches)
BL19302	42.9 (1.69)	BL19327	571.9 (22.51)
BL19303	71.2 (2.80)	BL19354	631.7 (24.87)
BL19304	104.1 (4.09)	BL19355	671.8 (26.45)
BL19305	141.0 (5.55)	BL19328	722.0 (28.42)
BL19310	194.1 (7.64)	BL19359	774.1 (30.48)
BL19311	214.0 (8.42)	BL19330	824.0 (32.44)
BL19312	251.0 (9.88)	BL19364	876.0 (34.50)
BL19313	287.0 (11.33)	BL19365	926.0 (36.46)
BL19314	324.0 (12.75)	BL19329	977.0 (38.46)
BL19315	361.0 (14.19)	BL19360	1028.0 (40.47)

Available in increments of 1 inch up to 80 inches.



DIMENSIONS ARE IN MILLIMETRES (INCHES)

Sampling of Part Numbers/Dimensions

Part #	Length (mm) (Inches)	Part #	Length (mm) (Inches)
BL19302	42.9 (1.69)	BL19327	571.9 (22.51)
BL19303	71.2 (2.80)	BL19354	631.7 (24.87)
BL19304	104.1 (4.09)	BL19355	671.8 (26.45)
BL19305	141.0 (5.55)	BL19328	722.0 (28.42)
BL19310	194.1 (7.64)	BL19359	774.1 (30.48)
BL19311	214.0 (8.42)	BL19330	824.0 (32.44)
BL19312	251.0 (9.88)	BL19364	876.0 (34.50)
BL19313	287.0 (11.33)	BL19365	926.0 (36.46)
BL19314	324.0 (12.75)	BL19329	977.0 (38.46)
BL19315	361.0 (14.19)	BL19360	1028.0 (40.47)

Available in increments of 1 inch up to 80 inches.