

## LINEAR BACKLIGHT

SERIE-BL193

BL193 linear backlight



### PRODUCT DESCRIPTION

Our Medium Intensity Linear Backlights provide rugged construction for demanding environments.


Medium intensity illumination with low power input requirements.

Multiple wavelengths available with very consistent illumination over the entire active area.

Available in 1" (25mm) increments with lengths up to 80.5" (2044mm).

### SPECIFICATIONS


<b>Approvals</b>	CE, RoHS
<b>Feed</b>	C1, C5, IC, I3, I3S, 24, M12
<b>IP Class</b>	IP64
<b>Life Span</b>	50000 h
<b>Temperature range from</b>	0 °C
<b>Temperature range to</b>	60 °C
<b>Wave-Length</b>	WHI, 470, 520, 660, 880



Sampling of Part Numbers/Dimensions

Part #	Length in mm (inches)	Part #	Length in mm (inches)
BL19302	42.9 (1.69)	BL19322	875.0 (34.45)
BL19304	71.7 (2.82)	BL19324	927.1 (36.50)
BL19306	104.5 (4.11)	BL19326	979.1 (38.55)
BL19308	151.3 (5.96)	BL19328	1031.1 (40.60)
BL19310	198.1 (7.80)	BL19330	1083.1 (42.64)
BL19312	244.9 (9.64)	BL19332	1135.1 (44.69)
BL19314	291.7 (11.48)	BL19334	1187.1 (46.74)
BL19316	338.5 (13.33)	BL19336	1239.1 (48.78)
BL19318	385.3 (15.17)	BL19338	1291.1 (50.83)
BL19320	432.1 (16.99)	BL19340	1343.1 (52.87)
BL19322	478.9 (18.85)	BL19342	1395.1 (54.92)

Available in increments of 1 inch up to 80 inches.



Sampling of Part Numbers/Dimensions

Part #	Length in mm (inches)	Part #	Length in mm (inches)
BL19302	42.9 (1.69)	BL19322	875.0 (34.45)
BL19304	71.7 (2.82)	BL19324	927.1 (36.50)
BL19306	104.5 (4.11)	BL19326	979.1 (38.55)
BL19308	151.3 (5.96)	BL19328	1031.1 (40.60)
BL19310	198.1 (7.80)	BL19330	1083.1 (42.64)
BL19312	244.9 (9.64)	BL19332	1135.1 (44.69)
BL19314	291.7 (11.48)	BL19334	1187.1 (46.74)
BL19316	338.5 (13.33)	BL19336	1239.1 (48.78)
BL19318	385.3 (15.17)	BL19338	1291.1 (50.83)
BL19320	432.1 (16.99)	BL19340	1343.1 (52.87)
BL19322	478.9 (18.85)	BL19342	1395.1 (54.92)

Available in increments of 1 inch up to 80 inches.

