

## NUVO-5000LP -SERIES INDUSTRIAL COMPUTERS

N5002LP-I7TE  
NEOU 5002LP I7TE



- Intel® 6th Gen. Core™ processor
- Low profile compact design
- 1x HotSwap and 1x fixed 2.5" HDD/SSD
- Up to 6 GigE-ports, 4 of which PoE supported

### PRODUCT DESCRIPTION

Nuvo-5002LP/5006LP is the low-profile version of Nuvo-5000 family. It features a low-profile chassis, which reduces its height to 77 mm, and remains extraordinary 25°C to 70°C operating temperature. For those demanding varied computing power, Nuvo-5002LP/5006LP supports socket-type CPU for flexible CPU installation. You can choose Intel® 6th Gen Core™ i7/i5/i3, from 35W to 65W TDP, according to your performance consideration and operating environment.

Nuvo-5002LP/5006LP fanless embedded computer inherits comprehensive I/O functions, such as GbE, USB3/USB2, COM and VGA/DVI/DP, from Nuvo-5000E/P. It also incorporates Neosys' MeziO™ interface for further I/O expansion. By installing optional MeziO™ module, Nuvo-5002LP/5006LP turns immediately from a typical embedded controller to a ruggedized application platform including 11x COM ports, 32 DIO channels, ignition power control, or your customized application-specific I/O.


Features:

- Intel® 6th Gen Core™ i7/i5/i3 35W/65W socket-type CPU
- MeziO™ interface for easy function expansion
- Rugged, wide temperature range from -25°C to 70°C fanless operation
- Up to 6x GigE ports, supporting 9.5 KB jumbo frame
- Up to 32 GB, DDR4-2133 SODIMM
- One hot-swappable 2.5" HDD/SSD and one fixed 2.5" HDD/SSD, supporting RAID 0/1
- Accommodates two 2.5" SATA HDD/SSD with RAID 0/1
- VGA/DVI/DP triple independent display, supporting 4K2K
- 77 mm low-profile design


## SPECIFICATIONS

<b>12834_Computertype</b>	Industrial
<b>AMT</b>	Intel® AMT 11
<b>Chipset</b>	Intel® Q170 Platform Controller Hub
<b>DC Input</b>	1x 3-pin terminal block
<b>Depth</b>	240 mm
<b>Height</b>	77 mm
<b>Memory RAM</b>	32 GB
<b>Processor</b>	Intel® Core™ i7-6700TE (8M Cache, 2,4/3,4 GHz, 35 W)
<b>Remote Control</b>	Yes
<b>Shock Resistance</b>	50 Grms (IEC60068-2-27)

<b>Supply Voltage DC Max</b>	35 V DC
<b>Supply Voltage DC Min</b>	8 V DC
<b>Temperature range bearing, from</b>	-40 °C
<b>Temperature range bearing, to</b>	85 °C
<b>Temperature range from</b>	-25 °C
<b>Temperature range to</b>	70 °C
<b>TPM</b>	TPM 2.0
<b>Vibration Resistance</b>	5 grms, 5-500 Hz, 3 axes (with SSD, according to IEC60068-2-64)
<b>Weight</b>	3.1 kg
<b>Width</b>	225 mm



Unit : mm



Unit : mm

