

HONSBERG - MR1K SERIES FLOW SWITCH

Piston

MR1K-015GM020
"Flow switch 1/2", 2-20 l/min"

- Switching Range 0,4..60 l/min H²O
- Water (oils, gases and aggressive media available on request)
- G¹/₄ up to G1
- Brass or Stainless Steel Wetted Parts
- Max Pressure 200 bar



PRODUCT DESCRIPTION

Model MR1K is a flow switch for liquids and air/gases. It is in a robust and compact version. The switch can be ordered in a large variety of special versions including integrated flow meter, selectable switching range and high pressure version.

SPECIAL VERSIONS

- **AIR VERSION**
- **INTEGRATED FLOW METER WITH VISUAL SCALE**
- **HIGH PRESSURE VERSION 500 BAR**
- **DOUBLE SWITCH HEADS**

SPECIFICATIONS

Contact Rating Max	50 VA
Flow Max l/min Double	30 l/min
Flow Range Max	20 l/min
Flow Range Min	2 l/min
IP Class	IP65
Material Bolt	Brass
Material of body	Nickel-plated brass
Material of seals	NBR
Materials Spring	Stainless steel 301

Pressure Range Max	200 bar
Temperature range of media from	-20 °C
Temperature range of media to	120 °C
Type of flow component	Flow Switches
Weight	1.3 kg
Viscosity Max	30 cSt
Viscosity Min	1 cSt
Voltage AC max	120 V

