

## HONSBERG - CRG SERIES FLOW SWITCH

Paddle

CRG-025HMS  
"Paddle switch 1"" DN25-DN300 0,6-90,8m3

- Switching Range 0,2...165,7 m3/h
- Water (oils and aggressive media available on request)
- Male Thread R1"
- Brass or Stainless Steel Wetted Parts
- Max Pressure 11 bar



### PRODUCT DESCRIPTION

Model CRG is a universal flow switch in brass or stainless steel. The same switch can be used for a large number of different pipe dimensions by using one or more paddle lengths. Four different paddle lengths are included.

## SPECIFICATIONS

<b>Contact Rating Max</b>	15 A
<b>Deviation max</b>	±15 %
<b>Flow Range Max</b>	165.7 m <sup>3</sup> /h
<b>Flow Range Min</b>	0.6 m <sup>3</sup> /h
<b>IP Class</b>	IP65
<b>Material Base</b>	Zink plated steel
<b>Material of connection</b>	Brass
<b>Materials Bellows</b>	Tombak
<b>Materials Cover</b>	ABS plastic
<b>Materials Paddle</b>	Stainless steel 316Ti
<b>Pipe dimension max</b>	200 mm
<b>Pipe dimension min</b>	25 mm
<b>Pressure Range Max</b>	11 bar
<b>Temperature range of media to</b>	120 °C

Type of flow component	Flow Switches
Viscosity	1 cSt
Voltage AC max	250 V
Weight	0.95 kg

