

BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA2000-50GM CAM GE M 2048*1088 50F BAS

- VGA to 20 Mpixels
- Frame Rate up to 340 fps
- · CMOS Sensors with NIR function
- Camera Link with PoCL
- · Very small housing





PRODUCT DESCRIPTION

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

SPECIFICATIONS

Sensor model	CMV2000
Resolution	2MP
Resolution Max	2048 x 1088 px
Frame Rate Max	50 fps
Mono/Color	Mono
Shutter type	Global
Pixel size	5.5 x 5.5
Sensor size	2/3"
Digital Outputs	1
Digital Inputs	1
Approvals	CE, FCC, GenlCam, GigE Vision, RoHS, UL, EAC
IP Class	IP30

Sensor supplier	CMOSIS
Sensor type	CMOS
Lens Barrel	C-mount
Weight	90 g
Length	42 mm
Width	29 mm
Height	29 mm
Power Consumption	2.5 W
Operating temperature	0°C 50°C

