

## MASS FLOW CONTROLLER SLAMF

SLAMF50

Thermal Mass Flow Controller SLAMF50

- Mass flow control and adjustment
- Zero stability: < 0.2% F.S. per year
- Broad array of communication options



### PRODUCT DESCRIPTION

Whether it's dust, moisture, temperature extremes or wash-down requirements, the SLAMf Series elastomer sealed thermal mass flow controllers and meters deliver the precise accuracy and long-term stability of our proven SLA5800 family of meters and controllers. A specially engineered NEMA4X/IP66 enclosure protects our advanced digital electronics and ensures stable, accurate measurement and control of your process-critical gas and liquid mass flows.

Features:

- NEMA4X / IP66 rated hardened enclosure
- Wide range of full scale flows - from 0.003 up to 2500 lpm (36,000 lpm for meters)
- Suitable for a broad range of temperature and pressure conditions
- Industry-leading thermal flow measurement sensor technology delivers excellent accuracy
- Programmable multi-gas/multi-range capabilities
- Advanced self-test routines and an independent diagnostic service port lets users troubleshoot or change flow conditions without removing the MFC from service
- Broad array of communication options including DeviceNet®, Profibus® and RS-485 plus analog interfaces

### SPECIFICATIONS

Atex Approvals	ATEX, IECEx
Control range	100:1 for FS from 1-50 slpm (50:1 for all other FS flows)
Diagnostics / Service Port	RS485 via 2.5mm jack
Differential Pressure Max	103.4 bar
Differential Pressure Min	0.35 bar
External Leakage	1x10 <sup>-9</sup> atm. cc/sec He
Pressure Range Max	310 bar
Response time	<1 s

