


DIRECT MOUNT SCREW TERMINALS

BAK, RD-D

1582.5

RK 50-D Blue, 50mm² Direct mount feed through terminal

- Compact 2.5mm -10mm² versions snap together
- Pre-labeled versions
- RK-D 50mm -240mm² Direct mount
- External cross connectors



PRODUCT DESCRIPTION

SPECIFICATIONS

Additional information	with housing pegs and allen screws
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Banded wire up to	11.8 x 5.0 mm
Color	Blue
Connections	2
Contamination degree	3
Country of origin	DE
Cross section single wire from	16 mm ²
Cross section single wire to	50 mm ²
Cross section stranded wire from	25 mm ²
Cross section stranded wire to	50 mm ²
Cross section stranded with ferrule from	25 mm ²
Cross section stranded with ferrule to	50 mm ²
Cross-Section	50 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2

GL test standard	IEC 60947-7-1:2002
Height TS 35/7.5	65.75 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	109 mm
Mounting	TS 35/7,5
Number of levels	1
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	10
Plug gauge acc. EN 60 947-1	B10
Rated Current CSA	150 A
Rated current CSAus	150 A
Rated Current IEC	150 A
Rated Current To UL	150 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	6
Rated wire cross section to (AWG)	1/0
Rated voltage CSAus	600 V
Rated Voltage IEC	1000 V
Rated Voltage To UL	600 V
Screw size	M 6
Screw type	Hexagon/Allen key
Stripping Length	27 mm
Tariff code	85369010
Torque max	6
Torque Min	3
UL test standard	UL 1059
Weight	111.2 g
Width	20 mm
Voltage CSA	600 V

