

DIRECT MOUNT SCREW TERMINALS

BAK, RD-D

1585.5

RK 240-D Blue, 240mm² Direct mount feed through terminal

- Compact 2.5mm -10mm² versions snap together
- Pre-labeled versions
- RK-D 50mm -240mm² Direct mount
- External cross connectors



PRODUCT DESCRIPTION

SPECIFICATIONS

Additional information	with housing pegs and allen screws
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Banded wire up to	20 x 12 mm
Color	Blue
Connections	2
Contamination degree	3
Country of origin	DE
Cross section single wire from	70 mm ²
Cross section single wire to	240 mm ²
Cross section stranded wire from	70 mm ²
Cross section stranded wire to	240 mm ²
Cross section stranded with ferrule from	70 mm ²
Cross section stranded with ferrule to	185 mm ²
Cross-Section	240 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2

GL test standard	IEC 60947-7-1:2002
Height TS 35/7.5	112.8 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	109 mm
Mounting	TS 35/7,5
Number of levels	1
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	5
Plug gauge acc. EN 60 947-1	B16
Rated Current CSA	370 A
Rated current CSAus	370 A
Rated Current IEC	380 A
Rated Current To UL	370 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	2/0
Rated wire cross section to (AWG)	500 Kcmil
Rated voltage CSAus	600 V
Rated Voltage IEC	1000 V
Rated Voltage To UL	600 V
Screw size	M 10
Screw type	Hexagon/Allen key
Stripping Length	38 mm
Tariff code	85369010
Torque max	20
Torque Min	10
UL test standard	UL 1059
Weight	352.4 g
Width	36 mm
Voltage CSA	600 V

