

SCREW TERMINAL COVERS AND WARNING SIGNS

AD, SAD, FAD, ZAD, TWMF

2955.0 AD 1/12/N/B, Yellow cover with black flash for 12mm wide RK16/35N

- Assembly cover profiles
- Individual terminal covers
- · Yellow or White
- Transparent cover profile
- RRK Cross connect covers



CONTACLIP

PRODUCT DESCRIPTION

Some regulations require that the mains power terminals must be covered.

This then discourages any operation of the screws or cross connector while 'Live'.

The EA , AD, SAD, FAD and ZAP covers are mainly available in yellow (labelled with a lightning flash) are used to cover the cross connect channel and screw holes of the terminal.

EA, AD & SAD covers are for the screw terminal range, where the FAD are for pressure spring and ZAD are for the tension spring range.

The BS 1 marker pen or the EMS labelling system can be used to label the white variants. The AD 4, is designed to cover four terminals of various sizes and is secured by two plastic screws.

The AQ 4 is used on the older RK series of scrfew terminals and covers the cross connect channel only, to cover the screw in cross connectors.

To complete the range the AD 3 is a transparent cover that can be cut to length and mounted using the TWMF partition plates.

SPECIFICATIONS

Additional information print: lightning flash Color Yellow Country of origin DE Flamklass UL94-V2 Length 26.5 mm Material Polyamide 6.6 Operating temperature from -40 °C Operating temperature to 105 °C Pack Size 20		
Country of origin DE Flamklass UL94-V2 Length 26.5 mm Material Polyamide 6.6 Operating temperature from -40 °C Operating temperature to 105 °C	Additional information	print: lightning flash
Flamklass UL94-V2 Length 26.5 mm Material Polyamide 6.6 Operating temperature from -40 °C Operating temperature to 105 °C	Color	Yellow
Length 26.5 mm Material Polyamide 6.6 Operating temperature from -40 °C Operating temperature to 105 °C	Country of origin	DE
Material Polyamide 6.6 Operating temperature from -40 °C Operating temperature to 105 °C	Flamklass	UL94-V2
Operating temperature from -40 °C Operating temperature to 105 °C	Length	26.5 mm
Operating temperature to 105 °C	Material	Polyamide 6.6
	Operating temperature from	-40 °C
Pack Size 20	Operating temperature to	105 °C
	Pack Size	20

Tariff code	85369010
Weight	0.58 g
Width	12 mm