


DIRECT MOUNT SCREW TERMINALS

BAK, RD-D

2173.2

BAK 4/5 Beige, 4mm², 5-pole Direct mount compact

- Compact 2.5mm -10mm² versions snap together
- Pre-labeled versions
- RK-D 50mm -240mm² Direct mount
- External cross connectors



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, KEMA KUR, EAC
Color	Beige
Connections	10
Contamination degree	3
Country of origin	DE
Cross section single wire from	0.2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.2 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.2 mm ²
Cross section stranded with ferrule to	4 mm ²
Cross-Section	4 mm ²
CSA test standard	C22.2 No 158
Distance to hole centres	37.7 mm
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
Height	23 mm
Insulation Material	Polyamide 6.6

KEMA KEUR test standard	EN 60947-7-1:2009
Length	44.8 mm
Mounting	Direct mount
Number of levels	1
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	50
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	25 A
Rated Current IEC	32 A
Rated Current To UL	30 A
Rated impulse voltage	6 kV
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Rated Voltage IEC	400 V
Rated Voltage To UL	300 V
Screw size	M 3
Screw type	Slotted
Stripping Length	9 mm
Tariff code	85369010
Torque max	1
Torque Min	0.5
UL test standard	UL 1059
Weight	26.2 g
Voltage CSA	300 V

