

## DATALOGIC - PROTECTIVE HOUSING SG-IP69K

SG-IP69K-1800  
IP69K tube for SG4 1800mm

- IP69K protective housing
- Available for heights 150–1800 mm
- Installation by user



### PRODUCT DESCRIPTION


Datalogic SG-IP69K protective housing is a PMMA acrylic tube to protect and seal light curtains of SG2-B, SG2-E, SG4-B and SG BODY COMPACT series. Thanks to SG-IP69K accessory the IP protection of the light curtain is increased from IP65 to IP67, IP68 and IP69K.


The Gore-Tex membrane on the caps prevents water or dirt entering as well as internal condensation. The connection cable for the light curtain is protected and kept in its place by a M16 metric chock that prevents the entry of water or dirt.

The SG-IP69K accessory is particularly suitable where high levels of humidity and temperature are present and machines or equipments are frequently washed with hot water (up to 80°C) at high pressure (up to 100 bars) and/or cleaned with detergents.



SG-IP69K is particularly suitable for FOOD industry applications:

- beverage production
- meat slaughter
- sausage production
- milk/cheese industry





MODEL	L (mm)
SS-PWLN 100	271.5
SS-PWLN 300	535.7
SS-PWLN 450	675.8
SS-PWLN 600	820.7
SS-PWLN 750	975.8
SS-PWLN 900	1130.7
SS-PWLN 1050	1270.7
SS-PWLN 1200	1420.8
SS-PWLN 1350	1570.7
SS-PWLN 1500	1720.8
SS-PWLN 1650	1870.8
SS-PWLN 1800	2020.8
SS-PWLN-2-090	915
SS-PWLN-2-1800	1115
SS-PWLN-4-090	1213.5
SS-PWLN-4-120	1613.5



MODEL	L (mm)
SS-PWLN 100	271.5
SS-PWLN 300	535.7
SS-PWLN 450	675.8
SS-PWLN 600	820.7
SS-PWLN 750	975.8
SS-PWLN 900	1130.7
SS-PWLN 1050	1270.7
SS-PWLN 1200	1420.8
SS-PWLN 1350	1570.7
SS-PWLN 1500	1720.8
SS-PWLN 1650	1870.8
SS-PWLN 1800	2020.8
SS-PWLN-2-090	915
SS-PWLN-2-1800	1115
SS-PWLN-4-090	1213.5
SS-PWLN-4-120	1613.5