

DATALOGIC - SG4-HAND

SG4-30-015-OO-E

SG4-30-015-OO-E 30mm Res Type

- Range up to 19 m
- Protection height 150-1800 mm
- Type 4 (PLe SIL 3)
- Compact profile



PRODUCT DESCRIPTION

SG4-Hand is a safety light curtain with a range of up to 19 metres.

This Type 4 light curtain maintains the highest safety level according to the latest safety standards EN ISO 13849-1 and EN 62061.

SG4-Hand curtain has built-in monitored reset, an input for monitoring of external contactors and two solid state safety outputs which are also electronically monitored.

This means that the SG4-Hand can work as a "standalone" unit if required and is not in need of any special control unit.

SPECIFICATIONS

Approvals	CE, cULus, TÜV
Cable Length Max	50 m
Conforming To	EMC, LVD, MD
Contact Current Max	0.5 A
DC	99 %
IP Class	IP65
Material of body	Aluminium
Mtffd	444 year
Number Of Beams	8
PL	e (EN ISO 13849-1)
Protection height	150 mm

Reaction time	9 ms
Scope	0,2-19 m
SIL	3 (EN IEC 62061)
T1 (Life Time In Years)	20
Temperature range from	0 °C
Temperature range to	55 °C
Type	Finger and hand protection
Voltage Tolerance	±20 %

