

## DATALOGIC - LIGHT CURTAINS SLIM

SL2-24-0750-E

957911540 Type 2 24mm Hand Res 750mm Prot

Height SLIM

- Range up to 6 m
- Slim profile 15x32 mm
- No dead zones
- Resolution 14, 24 and 34 mm
- Cascadable up to 3 units with 34 different protection heights at 30mm intervals



### PRODUCT DESCRIPTION

SLIM is a safety light curtain with a range of up to 6 metres designed to fit in the smallest spaces.

With 34 different protection heights at 30mm intervals it is one of the most flexible light curtains on the market.

This Type 4 light curtain maintains the highest safety level according to the latest safety standards EN ISO 13849-1 and EN 62061.

Datalogic's SLIM light curtain has built-in monitored reset, an input for monitoring of external contactors and two solid state safety outputs which are also electronically monitored.

This means that the SG4-Finger can work as a "standalone" unit if required and is not in need of any special control unit.

### SPECIFICATIONS

|                     |   |
|---------------------|---|
| Approvals           | CE, cULus, TÜV                                  |
| Cable Length Max    | 20 m  |
| Conforming To       | EMC, LVD, MD                                    |
| Contact Current Max | 0.3 A   |
| DC                  | 98,80 %   |
| Distance Max        | 6 m   |
| Function            | Calibration mode, Manual/Automatic restart, EDM |
| IP Class            | IP65  |
| Material of body    | Aluminium                                       |
| Mttfd               | 191 year  |

