

## DATALOGIC - LIGHT CURTAINS SLIM

SL4-34-0540-E

SAFETY LC SLIM 540/14mm/0,2-6m, Type 4

- Range up to 6 m
- Slim profile 15x32 mm
- No dead zones
- Resolution 14, 24 and 34 mm
- Cascadable up to 3 units with 34 different protection heights at 30mm intervals



### PRODUCT DESCRIPTION

SLIM is a safety light curtain with a range of up to 6 metres designed to fit in the smallest spaces.

With 34 different protection heights at 30mm intervals it is one of the most flexible light curtains on the market.

This Type 4 light curtain maintains the highest safety level according to the latest safety standards EN ISO 13849-1 and EN 62061.

Datalogic's SLIM light curtain has built-in monitored reset, an input for monitoring of external contactors and two solid state safety outputs which are also electronically monitored.

This means that the SG4-Finger can work as a "standalone" unit if required and is not in need of any special control unit.

### SPECIFICATIONS

<b>Approvals</b>	CE, cULus, TÜV
<b>Cable Length Max</b>	20 m
<b>Conforming To</b>	EMC, LVD, MD
<b>Contact Current Max</b>	0.3 A
<b>DC</b>	98,80 %
<b>Distance Max</b>	6 m
<b>Function</b>	Calibration mode, Manual/Automatic restart, EDM
<b>IP Class</b>	IP65
<b>Material of body</b>	Aluminium
<b>Mttfd</b>	191 year

