

## CONSTANT CURRENT LED DRIVERS

RCL040-0700B

LED driver 120 - 277 V AC/700 mA, 39,2 W

- Outputs: 250-1750 mA / 10-74 W
- Compact encapsulated assembly
- Long service life (50 000h @ 90 °C Tc)
- Different dimming options

### PRODUCT DESCRIPTION

### SPECIFICATIONS

|                                              |                             |
|----------------------------------------------|-----------------------------|
| Input voltage AC                             | 120-277 V                   |
| Input voltage ac min                         | 108 V AC                    |
| Input voltage ac max                         | 305 V AC                    |
| Output voltage (String)                      | 40-56 V DC                  |
| Output Current                               | 0.7 A                       |
| Power Max                                    | 39.2 W                      |
| Dimming                                      | 0-10V & vaihekulma (120Vac) |
| Length                                       | 87 mm                       |
| Width                                        | 60 mm                       |
| Height                                       | 27.2 mm                     |
| Weight                                       | 0.222 kg                    |
| IP Class                                     | IP20                        |
| Approvals                                    | CE, ENEC, UL                |
| Temperature range from                       | -30 °C                      |
| Temperature range to                         | 90 °C                       |
| Power Factor at 120 V AC, full load. Typical | 0.98                        |
| Power Factor at 230 V AC, full load. Typical | 0.97                        |