

## CONSTANT CURRENT LED DRIVERS

RSLD035-14

LED driver 120 - 277 V AC/700 mA, 34,3 W

- Outputs: 250-1750 mA / 10-74 W
- Compact encapsulated assembly
- Long service life (50 000h @ 90 °C Tc)
- Different dimming options

### PRODUCT DESCRIPTION

### SPECIFICATIONS

|                                              |                  |
|----------------------------------------------|------------------|
| Input voltage AC                             | 120-277 V        |
| Input voltage ac min                         | 90 V AC          |
| Input voltage ac max                         | 305 V AC         |
| Output voltage (String)                      | 35,0-49,0 V DC   |
| Output Current                               | 0.7 A            |
| Power Max                                    | 34.3 W           |
| Dimming                                      | 0-10V            |
| Length                                       | 70 mm            |
| Width                                        | 40 mm            |
| Height                                       | 27 mm            |
| Weight                                       | 0.142 kg         |
| IP Class                                     | IP20             |
| Approvals                                    | CB, CE, ENEC, UL |
| Temperature range from                       | -30 °C           |
| Temperature range to                         | 90 °C            |
| Power Factor at 120 V AC, full load. Typical | 0.9              |
| Power Factor at 230 V AC, full load. Typical | 0.9              |