

PROGRAMMABLE LED DRIVERS

RTLD040-900A-SA

LED driver 120 - 277V AC/150 mA - 900mA, 39,2W

- Programmable outputs: 150-2600 mA / 3,5-150 W
- Compact encapsulated assembly
- Long service life (100 000h @ 75 °C Tc)
- Different dimming options
- Programmable with Efore wired and wireless RFID tools and software



PRODUCT DESCRIPTION

Programmable LED drivers allow designers and assembly lines to personalize key output characteristics. Today's LED Lighting designers require more sophisticated technology from the power sources they choose in order to maximize the performance of their lighting fixture designs. Efore's ROAL brand of intelligent LED Drivers are packed with advanced features, unsurpassed efficiencies, and user-managed controls, allowing designers to effortlessly meet the challenges they face.

SPECIFICATIONS

Input voltage AC	120 - 277 V AC
Input voltage ac min	90 V AC
Input voltage ac max	305 V AC
Output voltage (String)	25 - 56 V DC
Output current	150 - 900 mA (ohjelmoitavissa)
Power Max	39.2 W
Dimming	0-10V (DTO)
Length	78 mm
Width	40 mm
Height	27 mm
Weight	0.17 kg
IP Class	IP64
Approvals	CB, CCC, CE, ENEC, UL
Temperature range from	-30 °C

Temperature range to	90 °C
Power Factor at 120 V AC, full load. Typical	0.98
Power Factor at 230 V AC, full load. Typical	0.97

