

## PROGRAMMABLE LED DRIVERS

RSOZ070-60-DALI

LED driver 120 - 277 V AC/350-2100mA, 70W

- Programmable outputs: 150-2600 mA / 3,5-150 W
- Compact encapsulated assembly
- Long service life (100 000h @ 75 °C Tc)
- Different dimming options
- Programmable with Efore wired and wireless RFID tools and software

### PRODUCT DESCRIPTION

Programmable LED drivers allow designers and assembly lines to personalize key output characteristics. Today's LED Lighting designers require more sophisticated technology from the power sources they choose in order to maximize the performance of their lighting fixture designs. Efore's ROAL brand of intelligent LED Drivers are packed with advanced features, unsurpassed efficiencies, and user-managed controls, allowing designers to effortlessly meet the challenges they face.

### SPECIFICATIONS

Input voltage AC	120 - 277 V AC
Input voltage ac min	108 V AC
Input voltage ac max	305 V AC
Output voltage (String)	30 - 56 V DC
Output current	350 - 2100 mA (ohjelmoitavissa)
Power Max	70 W
Dimming	DALI/PWM
Length	148 mm
Width	60 mm
Height	35 mm
Weight	0.345 kg
IP Class	IP20
Approvals	CE, ENEC, UL
Temperature range from	-30 °C
Temperature range to	85 °C
Power Factor at 120 V AC, full load. Typical	0.98

---

Power Factor at 230 V AC, full load. Typical

0.97

---

