

## ADVANCED ILLUMINATION - LL174 LINEAR LIGHTING

Expandable High Power Lighting

SERIE-LL174  
LL174 bar light



- Developed for large areas or Line scan applications
- Available in increments of 152 mm (6 inches) up to 1 219 mm (48 inches)



### PRODUCT DESCRIPTION

The LL174 is a high intensity bar light with a large degree of customisation. Available in 16 wavelengths, expandable up to 84" in 6" increments. There is optional heat sink for higher performance and/or high ambient temperature. 3 different lens options are also available, arrow, medium and wide beam spreads.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

All Wavelength options:

- UV - 365, 375, 385, 395
- Violet - 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

### SPECIFICATIONS

Approvals	CE, RoHS
Feed	C1, C5, IC, I3, I3S, 24
IP Class	IP50, IP65
Life Span	50000 h

Temperature range from	0 °C
Temperature range to	60 °C
Wave-Length	WHI, 365, 375, 385, 395, 405, 455, 470, 505, 530, 590, 625, 660, 730, 850, 940

UL174		
INSULATION	NON-SEALED	SEALED
UL174	175.7 (6.94)	176.8 (6.96)
UL17412	126.1 (5.004)	129.2 (5.086)
UL17413	479.6 (18.88)	481.2 (18.94)
UL17430	293.4 (11.55)	296.5 (11.68)
UL17435	535.6 (21.09)	538.7 (21.21)
UL17442	1098.2 (43.24)	1091.3 (42.96)
UL17445	1348.6 (53.10)	1343.7 (53.00)
UL17450	1331.0 (52.40)	1336.1 (52.60)
UL17460	1545.4 (60.84)	1546.5 (60.90)
UL17465	1697.8 (66.84)	1700.9 (66.94)
UL17472	1890.3 (74.44)	1883.3 (74.12)
UL17478	2052.6 (80.80)	2055.7 (80.90)
UL17480	2333.8 (91.84)	2336.1 (91.94)
LENGTH BY INCH (INCHES)		

