

## ADVANCED ILLUMINATION - AL126 LED BAR LIGHT

High dispersion, narrow

SERIE-AL126  
AL126 bar light

- Lighting with high intensity LEDs in compact format, only 20 mm wide
- Easy mounting with M4 nut channel
- Expandable in 2 inch increments from 2 "to 40"
- Available in WASH DOWN variant



### PRODUCT DESCRIPTION

The AL126 is a high dispersion LED bar light for reflective services and shorter working distances. It provides a narrower and less intense illumination area than AL116. Available with polarisation and diffusion light conditioning, along with a wide spectrum of wavelengths. IP65 compliant washdown option is also available.

This expandable compact bar light is pre-engineered for custom lengths in 2" increments up to 40".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 365, 375, 385, 395, 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI

For enquiries or quotes for wavelength, power options and sizes not listed here please [contact us](#).

### SPECIFICATIONS

Approvals	CE, RoHS
Feed	C1, C5, IC, I3, I3S, 24
IP Class	IP50, IP65
Life Span	50000 h
Temperature range from	0 °C

Temperature range to

60 °C

Wave-Length

WHI, 365, 375, 385, 395, 405, 455, 470, 530, 590, 625, 850, 940

