

USK PLASTIC CONNECTOR

5020.330.012

USK-M AD14 M12 connector grey

- Metric or PG thread
- For AIRflex®, KUW, K-series and GRS conduits





PRODUCT DESCRIPTION

USK plastic connector is made of polypropylene. Resistant against vibration and tension.

Products marked with * are NEMKO approved.

SPECIFICATIONS

Diameter	14 mm
Thread	M12x1,5 met. EN 60423
Pack Size	50
IP Class	IP54
Approvals	CSA 22.2, UL
Color	Grey
Temperature range from	-10 °C
Temperature range to	110 °C
Weight kg / 100 ± 10%	0,66
Material	Polypropylene
Type	USK-M
Fits to	AIRFLEX KUW-PU-AS, AIRFLEX KUW-PVZ-AS



USK-M

IP54-65	Ø	I mm	B mm	C mm	D mm
5020.330.012	14	8,0	25,0	12,0	43,0
5020.330.016	17	11,0	30,0	12,0	43,0
5020.330.020	21	15,0	35,0	13,0	44,0
5020.330.025	27	20,0	44,0	13,0	50,0
5020.330.032	36	27,0	54,0	15,0	51,0
5020.330.040	45	35,0	63,0	15,0	51,0
5020.330.050	56	44,5	77,0	16,0	58,0
5020.330.063	56	44,5	77,0	16,0	58,0

USK-P

IP54-65	Ø	I mm	B mm	C mm	D mm
5020.130.009*	14	9,0	25,0	10,0	41,0
5020.130.011*	17	11,0	30,0	10,0	41,0
5020.130.013	19	13,0	32,0	10,0	41,0
5020.130.016*	21	14,5	35,0	11,0	42,0
5020.130.021	27	19,5	44,0	11,0	48,0
5020.130.029	36	27,0	54,0	12,0	48,0
5020.130.036	45	36,0	63,0	12,0	48,0
5020.130.048	56	46,0	77,0	15,0	57,0