

LEGEND PLATES

Legend plate frames & inserts

LWP2 LEGEND FRAME (FOR PLATE LIA)

- Standard or large width frames
- 5 legend insert colour options
- Option for custom engraved texts
- Option for twin touch head



PRODUCT DESCRIPTION

Legend plate frames are mounted on the pushbutton head before installation in the panel and the inserts are simply snaped into the legend plate frame. Inserts are available in red, black, white, transparent or standard silver.

LIAx are standard width inserts for 2 lines of up to 13 characters.

LIBx are large width inserts for 2 lines of up to 18 characters.

LWP3 is the standard frame for LIAx inserts.

LWG3 is the standard frame for LIBx inserts.

LWP4 is a square profile frame for LIAx inserts


LWP2 is for twin & tripple touch heads for LIAx inserts.

All options below are for blank legend plate inserts but we can offer a wide range of pre engraved inserts of standard texts or symbols. We can also custom engrave the inserts to your exact requirement, please contact us for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C





Bestvering	Text Power C Pase Pase Pase Pase Pare Pare Pare Pare Pare Pare Pare Par	9 9	Kod 300 307 308 308 307 308 309 309	Text Start Stop Tripped Up 0 - 1 0 - 1 Start 1 - 0 - 1 1	Kod 301 302 335 335 081 083 091	
Auto 583 or 008 n 305 n 313 Stands	Rate Float Rom Runn Runn Slow	9 9	907 315 308 327 328	Stop Troped Up 0 - 1 0 - 1 - Start	502 3827 335 081 083	
2 328 or 308 301 303 n 313 Stand	Reset Resets Runn Runn Slow	10 10	315 306 327 3355	Tipped Up 0-1 0-1-Start	3327 335 061 083	
r 308 903 n 303 n 313 Sand	Reson Run Slow	9	306 327 3356	0 - 1 - Start	335 061 083	
er 308 303 n 303 n 313 Stand	Runn Runn Slow	9	327	0-1 0-1-Start	081	
1 303 n 313 Stand	Rumo Slow	9	3336	0 - I - Start	083	
n 313 Stand	Siow		3326		083	-
Stand			309	1-0-8		
Bestvering	ardsymboler ISC	O/DIN				1
			_			
and the second se		Symbol	Kod	Bearing	Synbol	Kod.
BO SAA	Poplat insta DO SAN		All.	Drgié 100 7 tr Dri el		AN
Rights, times BO 54D	Fights, tons (60.542)		894	00000 0075/09-40	٢	A29
durina 60.16		0	All.	Variety physics and 150:30.089-45	4	ÁS)
Pagina beneral IGC NI		0	AND	Haudinten 18234	(81)	AH
Automatist (peri plan i 100.07	Automatist (perijder samautomatist) 100.07		AU	Smighundyska 80.101		1004
Mariad kontrol (ICC 59			All	Belyaning 100 millio Decisio	0	ŝ
Inclusion data anteresis BO DE	ONSupportement BO 00		AND	Runsensense 160 107 OIN 175	C	1007
enditorior Dayra ann 60.71	(FOP Dayra ammuna 1907)		A10	Dia 100 109 DIN 264		:00
0 OvOFF sata - copital 80.71	CNUOFF auto - cogina antonivem 600.71		A21	5kg 50 100 08/268	(3)	100
Build stronerste, manual 00.727 SWI 198	Duis stroness, manual imput- 60 72/DH 198		A72	Guid Nami DN 105	60	001
Tillion	etundautouroho	-				-
			1 005	1 mm 1 mm 1		
	00 540 27 Biological Sciences 60 58 Biological Sciences 1 Biological Sciences 1 Advantant (para Marchines 100 58 Biological Sciences 1 Advantant (para Marchines 10 Biological Sciences 10 COVID* Advantant (para Marchines 10 COVID* Advantant (para Marchines 10 COVID* Advantant (para Marchines 10 COVID* Advantantantantantantantantantantantantanta	0100	disc 1 disc 1 f figurants € disc figurants €	Image Image <th< td=""><td>Image Image <th< td=""><td>1 Image of the second sec</td></th<></td></th<>	Image Image <th< td=""><td>1 Image of the second sec</td></th<>	1 Image of the second sec