

NON ILLUMINATED PUSHBUTTON

Flush Head

L21AA01
PUSH-B FLUSH SP-RTN RED

- IP66 / IP69K
- Spring return or latching
- Optional text or symbol



PRODUCT DESCRIPTION

Standard flush pushbutton heads that mount in a 22.5mm hole with protection rating IP66 / IP69K. Combine with separate clip and contact blocks to make complete pushbutton assembly. Available in multiple colours in spring return or latching. Supplied with a matt chrome bezel as standard. For black plastic bezel change the part number from L21xxx to L22xxx. Optional text or symbol can be added please enquire for more details.

SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Red
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP Class	IP66, IP69, IP69K
Protection Class	II (double insulated)
Recommended Torque	3 Nm
Temperature Range From	-25 °C
Temperature Range From Stock	-40 °C
Temperature Range To	70 °C
Temperature Stocks To	70 °C

Type/Model

Flush pushbutton

Weight

15,8 g

