

FILTER FAN FOR OUTDOOR USE - OLD VERSION

FF 018

01821.0-00

FF 018 Fan, 250 x 250 mm, 20m³/h, 230V ac, 50Hz, IP55

- Lockable lid
- Replaceable filter from the outside
- Protected against wind and weather
- IP55



PRODUCT DESCRIPTION

This filter fan FF018OUT / EF018OUT, is used mainly in outdoor outdoor appliances to ventilate excess heat. The hood is made of impact resistant plastic that is UV resistant and resistant to weather and wind.

By opening the lockable cover, the filter is for cleaning or replacement, and the protection class is due to the filter quality and the hood's design IP55.

SPECIFICATIONS

Air Capacity	20 m³/h
Air Volume Free Blowing	20 m³/h
Air Volume Free Blowing With F5 Filter	12 m³/h
Approvals	CE, cULus, EAC, RoHS, UL, UL E234324, UV - UL746C (f1), VDE
Color	Light Grey
Depth	127 mm
Filtering degree	98 %
Flamklass	UL94-V0
Frequenze	50 Hz
Height	224 mm
Humidity Storage	<90% RH
IP Class	IP55
Life span	50000 h

Material fan	Aluminium
Material of rotor	Plastic
Material Plastic Housing	Plastic
Number of fans	1
Operating Humidity	< 90% RH
Operational Temperature	-10°C ... +70°C
Power Consumption	100 mA
Power Consumption	15 W
Punching	125x125 mm
Sound level	40 dB
Storage temperature	-40°C ... +70°C
Structural Depth	65 mm
Weight	1,2 kg
Width	165 mm
Voltage max	230 V ac
Voltage min	230 V ac

