

LED BLOCKS

Screw terminals

33EABL
LED BLOCK SCREW 24V BLUE

- Long lifetime upto 100,000 hours
- 5 colour & voltage options
- Finger safe IP20 terminals



PRODUCT DESCRIPTION

LED blocks with screw terminal connection that snap directly in the centre position of 1, 3 or 5 position clips. Suitable for all illuminated pushbutton, selector switch, mushroom or pilot light heads. Available in colour options, red, green, yellow, white & blue. Available in voltage options 12-24Vac/dc, 48Vac/dc, 110Vdc, 130Vac & 230Vac. Long lifetime of up to 100,000 hours.

SPECIFICATIONS

| | |
|---|------------------------------|
| Approvals | UL 508, CSA 22.2, BV, CB, CE |
| Climate resistance cyclic damp heat | IEC 60068-2-3 |
| Climate resistance to sea air | IEC 60068-2-52 |
| Climate-resistant heat | IEC 60068-2-30 |
| Color | Blue |
| Connection solid wire max | 2,5 mm ² |
| Connection stranded wire with ferrule max | 1.5 mm ² |
| Connection stranded wire with ferrule min | 0.5 mm ² |
| Frequenze | 50/60 Hz |
| LED supply voltage | 12-24V AC/DC |
| LED Voltage Tolerance | ± 20% |
| Lifetime at rated supply voltage (25°C) | 50000 h |
| Power consumption | 25 mA ±20% |

| | |
|---|--------|
| Protection rating rear of panel | IP20 |
| Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3) | 4 kV |
| Rated insulation voltage Ui | 300 V |
| Temperature range bearing, from | -40 °C |
| Temperature range bearing, to | 70 °C |
| Temperature range from | -25 °C |
| Temperature range to | 70 °C |
| Torque max | 1,2 Nm |
| Weight | 17 g |

