

DATALOGIC - PROTECTIVE HOUSING SG-IP69K

SG-IP69K-150
IP69K tube for SG4 150mm

- IP69K protective housing
- Available for heights 150–1800 mm
- Installation by user



PRODUCT DESCRIPTION

Datalogic SG-IP69K protective housing is a PMMA acrylic tube to protect and seal light curtains of SG2-B, SG2-E, SG4-B and SG BODY COMPACT series. Thanks to SG-IP69K accessory the IP protection of the light curtain is increased from IP65 to IP67, IP68 and IP69K.

The Gore-Tex membrane on the caps prevents water or dirt entering as well as internal condensation. The connection cable for the light curtain is protected and kept in its place by a M16 metric chock that prevents the entry of water or dirt.


The SG-IP69K accessory is particularly suitable where high levels of humidity and temperature are present and machines or equipments are frequently washed with hot water (up to 80°C) at high pressure (up to 100 bars) and/or cleaned with detergents.


SG-IP69K is particularly suitable for FOOD industry applications:

- beverage production
- meat slaughter
- sausage production
- milk/cheese industry

SPECIFICATIONS

IP Class	IP67, IP68, IP69K
Material Protection	PMMA





MODEL	L (mm)
SD-PPM-100	275.5
SD-PPM-200	345.5
SD-PPM-400	475.5
SD-PPM-600	605.5
SD-PPM-700	675.5
SD-PPM-800	745.5
SD-PPM-1000	975.5
SD-PPM-1200	1105.5
SD-PPM-1500	1335.5
SD-PPM-1800	1565.5
SD-PPM-2000	1795.5
SD-PPM-2500	2295.5
SD-PPM-3000	2795.5
SD-PPM-4000	3795.5
SD-PPM-6000	5795.5
SD-PPM-8000	7795.5