

## TRIPLE TOUCH

Non Illuminated

L61BA22

TRIPLE TOUCH ARROW UP/DOWN/STOP

- IP66
- Flush pushbuttons
- Spring return
- Centre projecting button



### PRODUCT DESCRIPTION

Non illuminated triple touch heads that mount in a 22.5mm hole with protection rating IP66  
The buttons top and bottom are flush with a projecting centre button.

Combine with separate 333E clip and contact blocks to make complete triple touch assembly.  
Available in various colour / text / symbol combinations.  
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.  
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

### SPECIFICATIONS

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climate resistance cyclic damp heat	IEC 60068-2-3
Climate resistance to sea air	IEC 60068-2-52
Climate-resistant heat	IEC 60068-2-30
Color	Green/red/green
Function	Spring return
Illuminated	No
Impact resistance	IK05
IP Class	IP66

Recommended Torque	3 Nm
Temperature range bearing, from	-40 °C
Temperature range bearing, to	70 °C
Temperature range from	-25 °C
Temperature range to	70 °C
Type/Model	Triple touch

