



MICRO TWEEZER STATION CP-2E

CP-2B

Micro tweezer station CP-2E

- For SMC chip component removal
- PA120 micro tweezer handle
- Peak power 80W
- +90 °C...+450 °C



PRODUCT DESCRIPTION

The CP micro tweezer station comes with the Adjustable Micro Tweezers AM120. This is the fastest way to remove SMD chip components and small/medium SOP from PCB assemblies.

The Tweezers are suitable for C120 Cartridges. The station works with the JBC exclusive Heating System and the intelligent sleep & hibernation features. Using the menu you can personalize over 20 parameters.

It features a USB connector to update software, create graphs and manage parameters from a PC. A complete cleaning system with antisplash membrane and wiper with sponge is integrated.


Product Composition:

- 1 CP Control Unit
- 1 AM120-A Adjustable Micro Tweezers
- 1 C120002 Conical Bent Ø 0.2
- 1 S0354 Sponge 36x69mm
- 1 CL0160 ESD Safe Wiper for Compact Stations
- 1 CL6210 Brass Wool

SPECIFICATIONS

Ambient operating temperature	10-40
Dimensions	150x175x145
Input fuse	1 A
Output peak power	80 / 23.5
Supply voltage	230 V AC
Weight	2,7 kg

C120002



PA Micro tweezers

