

H07RN-F FINE-STRANDED CABLE, HARMONIZED TYPE

KAB01000210/04K
H07RN-F 2x1 mm²



- Heavy-duty rubber cable
- Suited for medium mechanical stress
- According to DIN VDE 0282 part 4, HD 22.4 S3 = IEC 60245-4
- Industrial applications

PRODUCT DESCRIPTION

H07RN-F is a heavy-duty rubber cable for various industrial applications in different environments. Suitable for dry, damp and wet conditions with temperatures ranging from -30° C to +60° C. H07RN-F withstands medium mechanical stress and it is applicable for fixed installations as well as different tools and machines.

SPECIFICATIONS

Number Of leads	2
Cross-Section	1 mm ²
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	Uo/U 450/750 V
Diameter Outer -5%	8,5 mm
Temperature Range The Use Of	60 °C
Temperature Range The Use Of	-25 °C
Temperature Range For Flexible Use	60 °C
Temperature Range Flexible Use Of	-25 °C
Copper Weight	19,2 kg/km
Weight	89 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Colour Outer Sheath	Black

Cable type

Rubber-insulated cable

