

KDS ACCESSORIES & TOOLS

28501.4

KDS-IVR 6/10, Locking frame, Black

- Seal insertion tool
- Hole punching tools
- EMC Cable shielding brackets
- Blanking plugs



PRODUCT DESCRIPTION

Accessories include:-

Seal insertion tool

The KDS BW 1 tool makes it easy to insert and remove the seals in to the KDS frames. The ergonomic grip and slotted shaft are ideal for confined spaces and makes sure the seal are pressed firmly in to the inlays

Shield-connection rails

The shield-connection rails, when used together with the wide range of shield-connection clips, enables cables to be shielded close to the entry/exit of the panel in a quick and easy process.

These rails are mounted to the inside of the enclosure using the same fixings as the KDS/KES frame.

Shield Clips

Several options are available, including the new SABK multi-clip, the traditional SAB spring clip and the SSAB screw clamp version.

The clips are available for cables of 1.5 mm ø to 32 mm ø.

Punching tools

A full range of sheet metal punches has been developed and are compatible with most of the leading manufacturers hydraulic pumps.

There are 2 versions designed for sheet steel and stainless steel, covering the 4 types of KDS frame cut-outs.

SPECIFICATIONS

| | |
|------------------------------------|-----------------|
| Approvals | cUL, UL |
| Color | Black |
| Country of origin | DE |
| cUL test standard | C22.2 No. 14-95 |
| Diameter of the screw holes | 5,5 mm |
| Flamklass | V-0 |
| Glass-fibre reinforced | Yes |

| | |
|----------------------------|-----------|
| Halogen free | Yes |
| Height | 11,5 mm |
| Installed height | 11,5 mm |
| Length | 105 mm |
| Material | Polyamide |
| Mounting | Screw |
| Number of screw holes | 4 |
| Operating temperature from | -40 °C |
| Operating temperature to | 120 °C |
| Pack Size | 10 |
| Silicone-free | Yes |
| Tariff code | 39259020 |
| UL test standard | UL 508 |
| Weight | 28 g |
| Width | 70 mm |