

## PR12 CAM SWITCHES

Screw mount

PR121101A8E

PR12 cam switch 16 A "0-1" 1-pole. screw mount

- Metal shaft
- Forced opened contacts
- Terminal screws in open position
- Special cam switches



### PRODUCT DESCRIPTION

### SPECIFICATIONS

Angle	45°
Area Cable Single Wire Max	4 mm <sup>2</sup>
Cable Area Multi-Conductor Max	2,5 mm <sup>2</sup>
Conventional free air thermal current I <sub>th</sub>	20 A
Function	Stable
Mounting	Screw on
Number Of Contacts	1
Number of poles	1
Number of positions	2
Plate	48x48 mm
Protection rating front of panel	IP40
Protection rating rear of panel	IP20
Rated insulation voltage ac (IEC 60947-1)	690 V
Rated insulation voltage ac (UL 508)	600 V
Rated insulation voltage U <sub>i</sub>	690 V
Rated operating current I <sub>e</sub> (AC15/230V)	6 A

<b>Rated operating current I<sub>e</sub> (AC21A/22A)</b>	16 A
<b>Rated operating current I<sub>e</sub> (DC-1/24 VDC)</b>	16 A
<b>Rated operating power (AC23A/3x230V)</b>	4 kW
<b>Rated operating power (AC23A/3x400V)</b>	7,5 kW
<b>Rated operating power (AC23A/3x500V)</b>	5,5 kW
<b>Rated operating power (AC23A/3x690V)</b>	4 kW
<b>Rated operating power (AC3/3x230V)</b>	3 kW
<b>Rated operating power (AC3/3x400V)</b>	4 kW
<b>Rated operating power (AC3/3x500V)</b>	5,5 kW
<b>Rated operating power (AC3/3x690V)</b>	3 kW
<b>Standards</b>	BV, CB, CCC, CE, CSA, IEC 60947-3 , IEC 60947-1, UL, UL 508
<b>Temperature range from</b>	-20 °C
<b>Temperature range to</b>	70 °C
<b>Type/Model</b>	ON-OFF switch

