

LINEAR BACKLIGHT

SERIE-BL193

BL193 linear backlight



PRODUCT DESCRIPTION

Our Medium Intensity Linear Backlights provide rugged construction for demanding environments.


Medium intensity illumination with low power input requirements.

Multiple wavelengths available with very consistent illumination over the entire active area.

Available in 1" (25mm) increments with lengths up to 80.5" (2044mm).

SPECIFICATIONS

Approvals	CE, RoHS
Feed	C1, C5, IC, I3, I3S, 24, M12
IP Class	IP64
Life Span	50000 h
Temperature range from	0 °C
Temperature range to	60 °C
Wave-Length	WHI, 470, 520, 660, 880



Sampling of Part Numbers/Dimensions

Part #	Length in inches (mm)	Part #	Length in inches (mm)
BL19302	42.9 (1.09)	BL19302	876.0 (22.14)
BL19304	71.7 (1.82)	BL19304	927.0 (23.44)
BL19306	104.9 (2.66)	BL19306	978.0 (24.74)
BL19308	131.0 (3.31)	BL19308	1029.0 (26.04)
BL19310	160.0 (4.06)	BL19310	1080.0 (27.34)
BL19312	189.0 (4.79)	BL19312	1131.0 (28.64)
BL19314	217.7 (5.53)	BL19314	1182.0 (29.94)
BL19316	246.0 (6.25)	BL19316	1233.0 (31.24)
BL19318	275.0 (7.00)	BL19318	1284.0 (32.54)
BL19320	303.0 (7.70)	BL19320	1335.0 (33.84)

Available in increments of 1 inch up to 80 inches.

