

1-PHASE FILTERS, FN2080-SERIES

FN2080-1-06

FILTER. 2-STAGE 1A/1-PHASE. FLAT PIN

- 1-16 A
- DC-400 Hz
- 2-stage
- High differential and common-mode attenuation, good low frequency attenuation



PRODUCT DESCRIPTION

SPECIFICATIONS

| | |
|--|---|
| Approvals | CSA 22.2 N°8 1986, EN60939, IEC60939, UL 1283 |
| Capacitance Cx | 0,33 µF |
| Capacitance Cy | 4,7 nF |
| Connection Thread | Flat plug |
| Flamklass | UL94-V2 |
| Frequenze | DC-400 Hz |
| High Potential Test Voltage "Hipot" | P->PE 2000 V AC, 2 s. P->N 1100 V DC, 2 s. |
| Inductance | 22 mH |
| Leakage Current Per Phase Max | 0,734 mA |
| MTBF (Mil-HB-217F) | 1650000 h @ 40° C, 230 V AC |
| Operating Voltage Max | 250 V AC |
| Rated Current, At 40 ° C | 1 A |
| Resistance | 1000 kΩ |
| Temperature range from | -25 °C |
| Temperature range to | 100 °C |
| Weight | 0,2 kg |

1 to 6 A types

